

Mail Lockers
Indoor/Outdoor
Technical Specifications

More than just smart lockers.

Mail lockers work in indoor and outdoor applications. They come equipped with extra small doors, convenient for depositing and picking up mail and small parcels.



The main console and add-on mail units are both available in full and half banks. Full banks consist of 27 (console) or 32 (add-on) doors. Half banks consist of 11 (console) or 16 (add-on) doors. Add-on units must be connected to a console unit.

All outdoor applications require a shelter to be installed on top.

Mail locker units connect to the internet via hardwired ethernet (recommended), Wi-Fi, or LTE and require a 110V (US) or 220V (UK/Europe) power supply. Additional units can be connected with RS 485A.



Dimensions and Construction

Color	Standard, Customizable
Standard Colors	RAL 7040  RAL 9018 
Weight (Pounds)	550 Pounds
Material	Cold Rolled Steel
Exterior Coating	Anti-corrosive Powder Coating
Interior Coating	Anti-corrosive Powder Coating
Thickness of the Steel	1.5 mm, Outdoor: 1.5mm, Anti-rust Steel
Type of Construction	Welded Steel Construction
Coasters/Leveling Feet	Fixed Stand Off/Optional Coasters or Levelers
Type of Door	Hinged, Opens Left to Right and Vice Versa
Security	Lockable Doors
Customizable	Yes
Night Lamp With Weather Shelter	For Outdoor Only
External Weather Shelter	For Outdoor Only
Opaque/Transparent Doors	Both

Electrical System Configuration and Installation Features

Power Supply (US)	110 V @ 15 amps Standard Supply
Power Supply (UK/Europe)	220V @ 15 amps Standard Supply
Operating Temperature (Indoor)	40°F-70°F
Operating Temperature (Outdoor)	-20°F-120°F
Installation Location	Indoor or Outdoor
Sensors	IR Sensors, Door Lock
Door Mechanism	Auto-open, Manual Close
Components (UL-Approved)	Power Supply, Trip Switch, Cables
Kiosk	AMOLED Tablet, Outdoor: Industrial-Grade Tablet

Connectivity

Connectivity	RS 485A/RS 232C
--------------	-----------------

Model

Available Models	11, 16, 27, 32 Doors
------------------	----------------------

Application

Residential, Retail, Corporate, University

Locker Bank Dimensions

Full Bank	Height	Width	Depth
27 Door (console)	78.35"	27.56"	19.69"
32 Door (add-on)	78.35"	27.56"	19.69"
Half Bank	Height	Width	Depth
11 Door (console)	78.35"	16.34"	19.69"
16 Door (add-on)	78.35"	16.34"	19.69"

Locker Door Configurations

Full Bank

27 Door (console)	27 Extra Small
-------------------	----------------

32 Door (add-on)	32 Extra Small
------------------	----------------

Half Bank

11 Door (console)	11 Extra Small
-------------------	----------------

16 Door (add-on)	16 Extra Small
------------------	----------------

Locker Door Dimensions

Size	Height	Width	Depth
XS	4.29"	10.43"	19.69"